

# PARTNER

CARE . TRUST . RESPONSIBILITY

## OT-200 Key Features

- Compact device with large 4.3" widescreen LCD
- Windows™ Mobile 6.5 Professional
- WLAN and GPRS/EDGE communication options
- GPS for location based services
- Ruggedized to IP54 and 1.2m drop test



OT-200  
Ordering Terminal

Partner Tech UK Corporation  
[www.partnertech-uk.com](http://www.partnertech-uk.com)

## OT-200: Revolutionary ordering terminal

The functionality and stylish appearance of the OT-200 is especially suited to the hospitality environment thanks to its compact size, lightweight design, and durability. Orders can be transmitted directly from the OT-200 to the bar or kitchen via WiFi, allowing your employees to spend more time with guests and less time walking back and forth.

With its touch-enabled 4.3" widescreen LCD, integrated WiFi, 1.2 metre drop test and IP54 rating, OT-200 is a cost effective handheld terminal which will enhance any hospitality solution.

- Reduces time spent on order taking and keying orders into POS system ~ information is directly transmitted via wireless to POS terminal and kitchen.
- Improves staff efficiency by eliminating need for waiters to go to kitchen to deliver orders
- Order processing time is immediate since kitchen receives order right away, allowing for quicker service, and higher table turnover
- Improved accuracy of order taking
- With its stylish and modern design, coupled with the latest technology, OT-200 will impress guests and enhance their customer experience



Add-on RFID module



Add-on MSR module



Packed with comprehensive accessories



Print orders directly to MP-300 mobile printer

Specification	
<b>CPU</b>	Samsung S3C6410 667 MHz processor
<b>Operating System</b>	Microsoft® Windows™ Mobile 6.5 Professional
<b>Display</b>	4.3" TFT LCD with Touch Screen, widescreen 800*480
<b>Memory</b>	256MB Flash, 256MB SDRAM
<b>Communication</b>	WiFi 802.11b/g
<b>Telecom standards (option)</b>	GPRS/EDGE
<b>GPS (option)</b>	Atheros
<b>Extension slot</b>	microSD card (supports SDHC)
<b>Interface</b>	Mini-USB 2.0
<b>Other</b>	G-sensor (for auto-rotation)      Speaker Vibrator motor (for alerts)      Earphone jack (3.5mm) Internal microphone      Microphone jack (2.5mm)
<b>Features</b>	Wireless roaming SSID Lock Battery cover safety protection Remote Desktop Lock screen
<b>Ruggedness</b>	IP54 1.2 meter drop tested
<b>Environmental</b>	Operating temperature: 0° C to 40° C Storage temperature:-20° C to 60° C
<b>Battery</b>	Rechargeable Li-ion battery 2300mAh (removable)
<b>Dimensions (WxLxH)</b>	82 x 133 x 19 mm
<b>Weight</b>	Approximately 245g with battery
<b>Optional modules</b>	RFID module (Mifare 13.56 MHz) MSR module (Track 1, 2, 3) Barcode scanner module (1D)
<b>Accessories</b>	AC adaptor, cradle, battery, stylus cord, hand strap, leather pouch, leather pouch cord, shoulder strap, spare high quality stylus
<b>Certifications</b>	RF: FCC / CE / SRRC / NCC EMC: FCC / CE / BSMI / VCCI Safety: BSMI / CB

\*specification subject to change without prior notice



### Partner Tech Corporation

**UK**  
T: +44 (0) 1928 579 707  
F: +44 (0) 1928 571 308  
E: sales@partnertech-uk.com

**Taiwan**  
T: +886 2 291 88500  
F: +886 2 291 53405  
E: sales@partner.com.tw

**USA**  
T: +1 949 598 1888  
F: +1 949 598 0088  
E: sales@partnertechcorp.com

**Europe**  
T: +49 (0)40 450 635 0  
F: +49 (0)40 450 635 130  
E: info@partner-tech.eu

**China**  
T: +86 21 676 9 6667  
F: +86 21 676 9 669  
E: sales@partnertech.com.cn