

OPL9728

Barcode laser scanner

IrDA

Serial cradle

Modem cradle

GSM cradle



+ Related products

OPL9712

- Data Collector
- Scanner Laser
- IrDA, Bluetooth



OPL9723

- Data Collector
- Barcode laser scanner
- IrDA
- 3 key operation



OPH1004

- Batch Terminal
- Barcode laser scanner
- IrDA
- IP 54



Operation

- CPU: 16-bit
- O/S: Proprietary
- Software: Programmable in C-language. Ansi-C Cross compiler obtainable. Software development kit free downloadable
- RTC: Supports year, month, day, hour, minute, second (leap year supported)

Memory

- FlashROM: 512 kB
- RAM: 1 MB

Display

- Type: Graphic LCD with backlight
- Size: 112 x 64 pixels
- Mode: Landscape / 180° rotation
- Font size: 6x6 / 6x12 / 8x8 / 8x16 dots

Operating indicators

- Visual: 1 LED (red/green/orange)
- Non-visual: Buzzer

Operating keys

- Entry options: 18 keys total, 12 key (alpha)numeric keypad, 2 function keys, 3 control keys, 1 scan key

Communication

- IrDA: Ver. 1.2, baudrate 2400 bps - 115.2 kbps

Power

- Rechargeable battery: Lithium-Ion 3.7V 600mAh
- Backup battery: Lithium rechargeable 3.5mAh
- Operating time: Ca. 45 hours (1 scan / 5 sec with backlight OFF, 1 sec laserbeam on, 0.2 sec green LED on, 0.2 sec buzzer on)
- Data retention time: Ca. 72 hours
- Charging method: Separate cradle CRD9720 series

Barcode scanner Optics

- Light source: 650 nm visible laser diode
- Scan method: Vibrating mirror
- Scan rate: 100 scans/sec
- Reading pitch angle: -25 to 0°, 0 to +25°
- Reading skew angle: -50 to -8°, +8 to +50°
- Reading tilt angle: -20 to 0°, 0 to +20°
- Curvature: R>15 mm (EAN8), R>20 mm (EAN13)
- Min. resolution at PCS 0.9: 0.15 mm / 6 mil
- Min. PCS value: 0.45
- Depth of field: At PCS 0.9, Code 39 60 - 300 mm / 2.36 - 11.81 in (1.0 mm / 39 mil), 35 - 210 mm / 1.38 - 8.27 in (0.5 mm / 20 mil), 35 - 120 mm / 1.38 - 4.72 in (0.25 mm / 10 mil), 35 - 70 mm / 1.38 - 2.76 in (0.15 mm / 6 mil)

Supported Symbolologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
- Postal code: Chinese Post, Korean Postal Authority code
- 2D code: Composite Codes, MicroPDF417, PDF417

Durability

- Temperature in operation: -5 to 40 °C / 23 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Humidity in operation: 20 - 80% (non-condensing)
- Humidity in storage: 20 - 90% (non-condensing)
- Ambient light immunity: White 3,000 lx max, Fluorescent 3,000 lx max, Direct sun 50,000 lx max
- Drop test: 1.5 m / 5 ft drop onto concrete surface
- Vibration test: 12 - 100 Hz with 2G for 1 hour
- Protection rate: IP 54

Physical

- Dimensions (w x h x d): 44 x 129 x 23 mm / 1.73 x 5.08 x 0.91 in
- Weight body: Ca. 105 g / 3.7 oz (incl. battery)
- Case: ABS, Lilacgrey

Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS, JIS-C-6802 Class 1, IEC 60825-1

Enclosed items

- Rechargeable battery
- Hand strap

Sold separately

- CRD9722 Cradle: Charging
- CRD9723RU Cradle: Serial communication, charging
- CRD9723RU1 Cradle: Multi-cradle, 1x communication, 5x charging
- CRD9723RU5 Cradle: Multi-cradle, 5x communication, 5x charging
- CRD9726 Cradle: Modem communication, charging
- CRD9727 Cradle: GSM communication, charging
- OPL9700 Nylon case with swivel clip & window
- OPL9700 Nylon case with swivel clip
- OPL9700 Nylon case with fixed clip

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariang
- **Brazil:** São Paulo

Opticon Sensors Europe B.V
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON
WWW.OPTICON.COM