



Smoke/wine shop



Handbag shop



Traffic



Express



Medical



★ XB-6266MBT

Specification

Performance Parameters

| | |
|------------------------|---|
| Light Sources: | 617nm LED Aimer,White LED |
| Supported Symbologies: | 1D:Codabar、 Code 11、 Code 39/Code 93、 UPC/EAN、 Code 128/EAN128、 Interleaved 2 of 5、 Matrix 2 of 5、 MSI Code、 Industrial 2 of 5、 GS1 Databa. 2D:QR code、 Data Matrix、 PDF417. |
| Scan Type : | Image CMOS |
| Scan Speed: | >25inch/63cm per second |
| Scan Method: | Manually/Automatical/Successive Scanning |
| Scan Angle: | Yaw 65°,Rotation 360°,Pitch 60° |
| Precision: | Code 39 4.8mil,UPC60% 5mil,PDF417 5mil,Datamatrix 7.5mil |
| Depth of scan field: | 5-390mm |
| Error Rate: | Less than 1/5million |
| Interface : | USB-HID,USB-COM,RS232 |
| Working Frenquency: | Bluetooth V2.1+EDR(Class 1) |
| Transmission Distance: | ≤100M(Open yard) |
| Storage Ability: | 512000Bytes |
| Pairing Model: | One to one |
| Receiving End : | Dedicated Bluetooth receiving base, Android、 IOS Mobile devices. |

Physical Parameters

| | |
|---------------|-----------------|
| Dimensions : | 85mm*62mm*154mm |
| Weight : | 190g |
| Material : | ABS+PC |
| able Length : | 1M |

Environmental Parameters

| | |
|-------------------------|---|
| Operating Temperature : | -20°C~60°C |
| Storage Temperature : | -40°C~70°C |
| Relative Humidity : | 5%~95% (Non-condensing) |
| Drop/Shock Resistance : | Withstands multiple times 3meters drops to concrete |

Electrical Parameters

| | | | |
|---------------------|-------------------------------------|------------------------|--------|
| Voltage : | DC5V±5% | Battery Working Time : | 5.5h |
| Operating Current : | 135mA | Charging Time : | 5h |
| Standby Current : | 2mA | Lithium battery : | 2200mA |
| Charging Model : | Point-contact charging through base | | |