



MC3390xR Long-range UHF RFID Reader

Best-in-class RFID read range with a powerful Android platform

Introducing the next evolution in long-range RFID readers. The MC3390xR integrated long-range handheld UHF/RAIN RFID reader brings a new level of efficiency and accuracy to inventory management, order fulfillment, cross-docking and more. You get the same proven lightweight ergonomic design of the successful MC3300R family, now with Zebra's latest, most powerful and secure Android architecture. The ultra-powerful processor, integrated NFC reader and 35% larger capacity battery boost task speed and ease of use. The integrated long-range antenna delivers best-in-class RFID read range and higher throughput, so inventory counts can be accomplished more quickly and accurately. With Zebra's signature rugged design, the MC3390xR is built for your semi-industrial environments. And you can create intuitive Android applications that use the MC3390xR's powerful computing platform, large touchscreen and physical keypad.



Low TCO with flexible deployment tools

Simplify application development with a common platform

If you are using other Zebra handheld RFID readers across your supply chain, you can streamline application development with a single software development kit. There's no need to learn a different app development framework or rewrite an application — use the same SDK for the MC3390xR, MC3330xR, MC3390R, MC3330R, RFD2000 and RFD8500 RFID Sled.

Simplify full-fleet rollouts with EMDK and RFID SDK for Xamarin

Xamarin's cross-development platform lets developers use their C# skills and tools to develop fast, beautiful apps for Android devices. With Zebra's EMDK and RFID SDK for Xamarin, it's easy to incorporate all the advanced enterprise features of the MC3390xR into your Xamarin apps. Our EMDK simplifies enterprise application design for faster, more cost-effective development cycles, while our RFID SDK for Xamarin allows you to use RFID apps you've developed for other Zebra devices on the MC3390xR.

Unparalleled data capture performance and flexibility

Best-in-class RFID read range and accuracy

The integrated long-range antenna can capture RFID tags more than 60 ft./18.2 m away — 200% farther than the next leading competitor. This reliable, long-range RFID performance enables more frequent and more accurate inventory-count operation, so you can better manage your on-the-floor, backroom and distribution inventory.

Superior sensitivity for greater accuracy

Zebra's high-performance ASIC radio technology provides superior sensitivity and greater read accuracy, delivering a read rate that is more than 25% faster and over 40% more accurate than other devices in this class.¹



Bring a new level of efficiency and accuracy to inventory, order fulfillment and cross-docking applications with the MC3390xR. For more information, visit www.zebra.com/mc33390xr

Integrated mid-range or long-range 1D/2D barcode scanning

Workers don't need different devices to capture RFID tags and barcodes — the MC3390XR can capture it all. Choose between a mid-range scan engine or the extended range scan engine that can capture barcodes from 3 in./7.62 cm to as far as 70 ft./21.4 m away. Both options offer Zebra's exclusive PRZM Intelligent Imaging technology for first time, every time capture of 1D and 2D barcodes, regardless of condition.

Easy-to-use locating technology

The MC3390XR can help pinpoint the location of a specific item. Item Finder mode uses audible and visual cues to quickly guide workers to the location of any desired item.

Capture multiple barcodes and entire forms with a single scan

Do you need to capture multiple barcodes on one or more labels on an item? The MC3390XR makes it easy. Workers can easily capture all the right barcodes on numerous labels, all with one press of the scan trigger.

Powerful platform for demanding enterprise applications**Built for semi-industrial environments**

The MC3390XR offers a 5 ft./1.5 m drop specification and with IP54 sealing, it can handle splashing liquid and dust. The Corning® Gorilla® Glass touchpanel and imager window bring maximum scratch-resistance and shatter-proofing to two of the most vulnerable device features. The result? Workers can drop the MC3390XR on concrete and use it in dusty areas — and still expect reliable operation.

Power full shifts with the class-leading 7000mAh battery

The new 7000mAh extended capacity battery is standard with every MC3390XR. More power means fewer battery changes, easier battery management and a smaller battery pool. And Zebra's PowerPrecision+ technology provides a full suite of metrics that make it easy to identify, remove and replace aging batteries.

Lightweight and streamlined design

The MC3390XR is one of the lightest UHF RFID readers in its class and is built for easy one-handed use, whether workers are right- or left-handed.

Unparalleled computing power

Power your most demanding apps of today and tomorrow with a superior processor and memory — every model offers an ultra-powerful 2.2 GHz octa-core processor and 4 GB RAM/32 GB Flash.

Backward compatible accessories

You can use most of your existing MC3200/MC3300/MC3300R accessories for a cost-effective upgrade. And choose from new accessories like the universal ShareCradle that simplifies backroom management.

Feedback for any environment

With high visibility LEDs, workers can easily keep track of charging status and confirm a task was completed, even in the noisiest environments. LEDs are located on both sides of the device to ensure visibility from any angle.

Integrated NFC for simple, split-second pairing

With a quick tap, workers can pair the MC3390XR with Zebra's family of ring scanners, mobile printers, and Bluetooth headsets. And you can also use the NFC reader for "tap to authenticate" applications, where workers simply tap their employee ID badge to log into authorized applications and resources.

Simplify data entry with a keypad and large touchscreen**The perfect combination: large touchscreen and keypad**

Whether your application requires touch or physical keypad input, we've got you covered. Your application can utilize the entire display, while the physical keypad provides the same familiar user input experience your workers have today. And with three different options, you can choose the right keypad for your data entry needs — alphanumeric, numeric and functional numeric.

The ultimate in Android support**The only device in this class to offer Android 10**

The most powerful version of Android yet, Android 10 makes the MC3390XR easier to use and even more secure. For your IT department, there are 50+ new security and privacy improvements.

A lifetime security guard for Android

With LifeGuard™ for Android™, you get the security updates you need to keep your MC3390XR RFID readers secure every day they are in service — along with an easy end-to-end control of the OS update process, plus built-in support for the next version of Android.

MC3390xR Specifications

Physical Characteristics	
Dimensions	6.45 in. L x 3.78 in. W x 10.67 in. D 164 mm L x 96 mm W x 271 mm D
Weight (with handstrap)	MC3390xR with SE4770: 26.2 oz./743 g MC3390xR with SE4850: 27.1 oz./769 g
Display	4-inch (800 x 480) WVGA; color display
Imager Window	Corning Gorilla Glass
Touchpanel	Corning Gorilla Glass touch panel with air gap; supports dual input mode with finger, gloved finger and stylus (conductive stylus sold separately)
Backlight	LED backlight
Expansion Slot	User accessible MicroSD with 32 GB SDHC and up to 512 GB SDXC
Network Connections	USB 2.0 High Speed (host and client), WLAN and Bluetooth
Notification	Side LEDs and audible tone
Keypad	Numeric (29 key), Function Numeric (38 key), Alpha Numeric (47 key)
Voice	PTT Express and Workforce Connect PTT Pro (Internal speaker, microphone and Bluetooth wireless headset support)
Audio	Built-in speaker and microphone
Performance Characteristics	
CPU	Qualcomm Snapdragon™ 660 octa-core 2.2 GHz
Operating System	Android 10 with Zebra's Restricted Mode for control over GMS and other services; will support future Android releases
Memory	4 GB/32 GB Flash
Power	All models ship with rechargeable Li-Ion, 3.6V, 7000mAh PowerPrecision+ battery; full charge under five (5) hours; hot swap support with temporary WLAN/Bluetooth session persistence Backwards compatibility with 5200mAh (2X) batteries
User Environment	
Operating Temp.	-4° F to 122° F/-20° C to 50° C
Storage Temp.	-40°F to 158°F/-40°C to 70°C
Humidity	5% to 95% RH (non-condensing)
Drop Specifications	Multiple 5 ft./1.5 m drops to concrete over the entire operating temperature range
Tumble Specification	1,000 1.6 ft./0.5 m tumbles
Sealing	IP54
Vibration	Sine: 4g's peak, 5hz to 2khz, Random: .04g ² /hz, 20hz to 2khz
Thermal Shock	40° F to 158° F/-40° C to 70° C
Electrostatic Discharge (ESD)	+/- 15kV air, +/-8kV contact discharge +/-8kV indirect contact discharge

Interactive Sensor Technology (IST)	
Motion Sensors	3-axis accelerometer with MEMS gyroscope
RFID	
Standards Supported	EPC Class 1 Gen2; EPC Gen2 V2; ISO-18000-63
RFID Engine	Zebra Proprietary Radio Technology
Fastest Read Rate	900+ tags/sec
Nominal Read Range	~60+ ft./~18.2+ m
RFID Power Output	0 dBm to +30 dBm
RFID Antenna Type	Integrated Linear Polarized
Frequency Range	865-928MHz *Specific regional and country settings supported upon country selection
Barcode Scanning	
Scan Engines	SE4770 with LED Aimer SE4850 Extended Range Imager
Wireless LAN	
Radio	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/l/v/w/m/c ² ; Wi-Fi™ certified; IPv4, IPv6, 2x2 MU-MIMO
Data Rates	5GHz: 802.11a/n/ac — up to 866.7 Mbps 2.4GHz: 802.11b/g/n — up to 300 Mbps
Operating Channels (depending on Regulatory)	Channel 1-13 (2412-2472 MHz): 1,2,3,4,5,6,7,8,9,10,11,12,13 Channel 36-165 (5180-5825 MHz): 36,40,44,48,52,56,60,64,100,104,108,112,116,120,124,128,132,136,140,144,149,153,157,161,165 Channel Bandwidth: 20, 40, 80 MHz Actual operating channels/ frequencies and bandwidths depend on regulatory rules and certification agency.
Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA3 ² Personal (SAE); WPA/WPA2 Enterprise (TKIP and AES); WPA3 ² Enterprise (AES) — EAP-TTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-EAP-GTC, LEAP and EAP-PWD; WPA3 ² Enterprise 192-bit Mode (GCMP-256) — EAP-TLS; Enhanced Open (OWE)
Certifications	WFA (802.11n, WMM-PS, 801.11ac, PMF); WiFi Direct WMM-AC, Voice Enterprise
Fast Roam	PMKID caching; Cisco CCKM; 802.11r; OKC
Wireless PAN	
Bluetooth	Class 2, Bluetooth v5.0 with BR/EDR and Bluetooth Low Energy (BLE) Support
Accessories	
Single slot cradle with spare battery charger; 4-slot charge only cradle with 4-slot battery charger; 4-slot Ethernet cradle with 4-slot battery charger; 5-slot charge only cradle; 5-slot Ethernet cradle	

MC3390xR vertical markets and applications:

Supply Chain/ Transportation and Logistics

- Cross-docking
- Item tracking/ locationing

Warehousing

- Inventory/cycle counting
- Automatic replenishment
- Receiving/shrink control
- Item tracking/ locationing
- Omni-channel order fulfillment

Manufacturing

- WIP
- Parts and finished good inventory

MC3390xR Specifications (continued)

Regulatory	
EMI/EMC	FCC Part 15 Subpart B Class B; ICES 003 Class B; EN 301 489-1; EN 301 489-3; EN 55024; EN 55032 Class B
Electrical Safety	UL 60950-1, CAN/CSA C22.2 No. 60950-1, IEC 60950-1, EN 60950-1
RF Exposure	EU: EN 50364, EN 62369-1, EN 50566, EN 62311 USA: FCC Part 2, 1093 OET Bulletin 65 Supplement 'C' Canada: RSS-102

Environmental Compliance	
Environment	
<ul style="list-style-type: none"> RoHS Directive 2011/65/EU; Amendment 2015/863 REACH SVHC 1907/2006 	
A complete list of product and materials compliance, please visit: www.zebra.com/environment	

Warranty	
Subject to the terms of Zebra's hardware warranty statement, the MC3390XR is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, please visit: http://www.zebra.com/warranty	

Recommended Services	
Zebra OneCare Essential and Select: Maximize Zebra device availability, device value and operational efficiency with these fully-featured support services that set the industry bar for support.	
Zebra VisibilityIQ™ Services: Improve device value with Zebra's optional VisibilityIQ™ Services. VisibilityIQ gives the data-driven, actionable insight to get the most from your devices, workers and daily tasks. VisibilityIQ™ Foresight aggregates big data onto a single, color-coded, cloud-based pane of glass, translating it into actionable insight to streamline workflow. VisibilityIQ™ DNA provides a view into key DNA tools, and VisibilityIQ™ OneCare® cloud-based dashboard offers visibility into repairs, tech support, software security status and more.	

Footnotes	
1. Based on Zebra test results from specific use cases	
2. Feature available Q4 2020	
Specifications subject to change without notice.	

Mobility DNA	
Mobility DNA solutions help you get more value out of our mobile computers by adding functionality as well as simplifying deployment and management of our mobile devices. For more information on these Zebra-only features, please visit www.zebra.com/mobilitydna	
Mobility DNA is available on Android only. Features may vary by model and a Support Contract may be required. To learn what solutions are supported, please visit: https://developer.zebra.com/mobilitydna	



NA and Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
contact.apac@zebra.com

EMEA Headquarters
zebra.com/locations
contact.emea@zebra.com

Latin America Headquarters
+1 847 955 2283
la.contactme@zebra.com